



Model Number L5332-2 Tri-Filter

Rev.-
1/04/06

Features:

- Cavity Design
- Low Loss

Applications:

- Maritime
- Airborne
- Mobile
- Timing
- Test Equipment

Package size:

- 1.25 x 3.8 x 5.8"

(Please see outline for exact dimensions)



Specifications: (+25C)

Passband	1575.42 +/- 10 MHz 2067.5 +/- 40 MHz 2441.75 +/- 40 MHz
Insertion Loss	1.0 dB @ Fc
VSWR	1.3:1 @ Fc
3 dB Bandwidth	+/- 12 MHz Nominal (1575.42 MHz) +/- 45 MHz Nominal (2067.5 and 2441.75)
40 dB Bandwidth	+/- 33 MHz Max (1575.42 MHz) +/- 70 MHz Max (2067.5 and 2441.75)
60 dB Bandwidth	+/- 53 MHz Max (1575.42 MHz) +/- 95 MHz Max (2067.5 and 2441.75)
Connectors	1 SMA Female (in) 1 SMA Female Out



Delta Microwave

1301 Vanguard Dr.
Oxnard, CA. 93033

Phone: 805.240.1044
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

--	--

By

Checked