



Model Number S5406 Triplexer

Rev -
1/03/06

Features:

- Cavity Design
- Low Loss

Applications:

- Telemetry
- Test Equipment

Package size:

- 1.75 x 3.0 x 3.5"

(Please see outline for exact dimensions)



| Specifications: (+25C) | Channel 1 | Channel 2 | Channel 3 |
|---------------------------|------------------|------------------|------------------|
| Passband | 1435 to 1540 MHz | 1760 to 1850 MHz | 2200 to 2300 MHz |
| Insertion Loss | 0.35 dB Max | 0.35 dB Max | 0.35 dB Max |
| VSWR | 1.2:1 Max | 1.2:1 Max | 1.2:1 Max |
| Isolation | 25 dB Min | 25 dB Min | 25 dB Min |
| Ultimate Attenuation | 25 dB Min | 25 dB Min | 25 dB Min |
| Phase Deviation | 1° / MHz Max | 1° / MHz Max | 1° / MHz Max |
| Connectors | SMA Female | SMA Female | SMA Female |



Delta Microwave

1301 Vanguard Dr.
Oxnard, CA. 93033

Phone: 805.240.1044
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

| | |
|--|--|
| | |
|--|--|

By

Checked